Sant Longowal Institute of Engineering and Technology, Longowal, Distt. Sangrur (Deemed to be University) (Established by Govt. of India)

Quotation Notice

Quotation are invited from working contractors registered with CPWD, State PWD, MES, PUDA/Central Public Sector undertaking having valid license under Contractor Labour (Regulation & Abolition) Act, 1970 and experience of having successfully completed works during the last 7 years ending last day of the month previously to one in which applications are invited:

Three similar completed work each costing not less than the amount equal to 40% of estimated cost put to tender or Two similar completed works, each costing not less than the amount equal to 60% of the estimated cost put to tender or One similar completed work of costing not less than the amount equal to 80% of the estimated cost put to tender with some Central Government Department/State Government Department/Central Autonomous Body/Central Public Sector undertaking.

Sr. No.	Name of Work	DNIT Amount in (Rs.) Laces	Earnest Money Deposit is 2% of the DNIT amount (Rs. in Rupees)	Cost of Quotation Documents in (Non- refundable)	Time Period	Tender processing fee (Rs.)	Schedule of Quantities
1	Partition of faculty room at the ground floor of Computer Block at SLIET, Longowal	36,587.00	Nil	Nil	15 Days	Nil	Annexure-

The Quotation documents will be available only on the Institute's website and should be submitted in the estate office (Civil Wing).

Schedule of Quotations

	Quotation for ding	Last date of Submission of Quotation	Date and time of opening of Quotation in Estate Office, SLIET,		
From	To		Longowal		
01.11.2017	08.11.2017	08.11.2017 before 5:00 PM	09.11.2017 at 12: 30 PM		

Eng.-In-Charge

Annexure- 'A'

S.No.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
1	Brick work with common burnt clay F. P. S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in: 6.4.1 Cement mortar 1:4 (1 cement: 4 coarse sand)	Cum	3.50		
2	Providing and fixing T-iron frames for doors, windows and ventilators of mild steel T e-sections, joints mitred and welded, including fixing of necessary but thinges and screws and applying a priming coat of approved steel primer. 10.13.1 Fixing with 15x3 mm lugs 10 cm long embedded in cement concrete block 15x10x10 cm of C.C. 13:6 (1 Cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size)	Kg	20.00		
3	Providing and fixing ISI marked flush door shutters conforming to IS: 2202 (Part I) non-decorative type, core of block board construction with frame of 1st class hard wood and well matched commercial 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters: 9.21.1 35 mm thick including ISI marked S tainless Steel butt hinges with necessary screws	Sqm	2.50		
4	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-	Sqiii	2.30		
5	charge. 5.7.4 In cement mortar Removing mortar from bricks and cleaning bricks including stacking within a lead of 50 m (stacks of cleaned bricks shall be measured):	Cum	0.50		
	15.8.3 From brick work in cement mortar	1000 nos.	0.50		
6	CEMENT PLASTER (IN COARSE SAND) 12 mm cement plaster of mix: 13.4.2 1:6 (1 cement: 6 coarse sand)	Sqm	15.50		
7	15 mm cement plaster on rough side of single or half brick wall of mix: 13.5.2 1.6 (1 cement: 6 coarse sand)	Sqm	15.50		
8	INTERIOR FINISHING White washing with lime to give an even shade: 13.37.1 New work (three or more coats)	Sqm	31.00		
9	Applying priming coat: 13.50.1 With ready mixed pink or Grey primer of approved brand and manufacture on wood work (hard and soft wood)	Sqm	5.00		
10	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: 13.62.1 Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture	Sqm	5.00		
11	Providing and fixing aluminium sliding door bolts, ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868), transparent or dyed to required colour or shade, with nuts and screws etc. complete: 9,96.2 250x16 mm	Each	1.00		
12	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete: 9.97.3 200x10 mm	Each	2.00		
13 9.160	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary series set, complete: 9.100.1 125 mm	Each	2.00		
		Lucii	2.00		

Eng.-In-Charge