

**Sant Longowal Institute of Engineering and Technology,  
Longowal, Distt. Sangrur  
(Deemed to be University)  
(Established by Govt. of India)**

**Quotation Notice**

Quotation are invited from working contractors registered with CPWD, State PWD, MES, PUDA/Central Public Sector undertaking having valid license under Contractor Labour (Regulation & Abolition) Act, 1970 and experience of having successfully completed works during the last 7 years ending last day of the month previously to one in which applications are invited:

Three similar completed work each costing not less than the amount equal to 40% of estimated cost put to tender or Two similar completed works, each costing not less than the amount equal to 60% of the estimated cost put to tender or One similar completed work of costing not less than the amount equal to 80% of the estimated cost put to tender with some Central Government Department/State Government Department/Central Autonomous Body/Central Public Sector undertaking.

Sr. No.	Name of Work	DNIT Amount (Rs. In Rupees)	Earnest Money Deposit is 2% of the DNIT amount (Rs. in Rupees)	Cost of Quotation Documents in (Non-refundable)	Time Period	Tender processing fee (Rs.)	Schedule of Quantities
1	Provision of Dustbin for Boys Hostel No. 9 & 10 at SLIET, Longowal	93,738.00	Nil	Nil	03 Months	Nil	Annexure- 'A'

The Quotation documents will be available only on the Institute's website and should be submitted in the estate office (Civil Wing).

**Schedule of Quotations**

Availability of Quotation for Bidding		Last date of Submission of Quotation	Date and time of opening of Quotation in Estate Office, SLIET, Longowal
From	To		
29.01.2018	05.02.2018	05.02.2018 before 5:00 PM	06.02.2018 at 3: 00 PM

**Eng.-In-Charge**

**Annexure- 'A'****Name of Work: Provision of Dustbin for Boys Hostel No. 9 & 10 at SLIET, Longowal.**

<b>S.No.</b>	<b>DESCRIPTION OF ITEM</b>	<b>UNIT</b>	<b>QTY.</b>	<b>RATE</b>	<b>AMOUNT</b>
<u>1</u>	Earth work in surface excavation not exceeding 30 cm in depth but exceeding 1.5 m in width as well as 10 sqm on plan including getting out and disposal of excavated earth upto 50 m and lift upto 1.5 m, as directed by Engineer-in-Charge: 2.1.1 All kinds of soil	Sqm	31.00		
<u>2</u>	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 4.1.5 1:3:6 (1 Cement : 3 coarse sand (zone-III) : 6 graded stone aggregate 20 mm nominal size)	Cum	1.00		
<u>3</u>	Making plinth protection 50mm thick of cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) over 75mm thick bed of dry brick ballast 40 mm nominal size, well rammed and consolidated and grouted with fine sand, including necessary excavation, levelling & dressing & finishing the top smooth.	Sqm	12.00		
<u>4</u>	Brick work with common burnt clay F .P .S. (non modular) bricks of class designation 7.5 in foundation and plinth in: 6.1.2 Cement mortar 1:6 (1 cement : 6 coarse sand)	Cum	1.50		
<u>5</u>	Brick work with common burnt clay F .P .S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in : 6.4.2 Cement mortar 1:6 (1 cement : 6 coarse sand)	Cum	2.50		
<u>6</u>	Brick edging 7cm wide 11.4 cm deep to plinth protection with common burnt clay F .P .S. (non modular) bricks of class designation 7.5 including grouting with cement mortar 1:4 (1 cement : 4 fine sand)	Mtr.	16.00		
<u>7</u>	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete	Kg	150.00		
<u>8</u>	Providing and fixing 1mm thick M.S. sheet door with frame of 40x40x6 mm angle iron and 3 mm M.S. gusset plates at the junctions and corners, all necessary fittings complete, including applying a priming coat of approved steel primer . 10.5.2 Using flats 30x6mm for diagonal braces and central cross piece	Sqm	1.50		
<u>9</u>	Brick on edge flooring with bricks of class designation 7.5 on a bed of 12 mm cement mortar, including filling the joints with same mortar , with common burnt clay non modular bricks: 11.1.1 1:4 (1 cement : 4 coarse sand)	Sqm	15.00		
<u>10</u>	Cement concrete flooring 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry , but excluding the cost of nosing of steps etc. complete. 1 1.3.1 40 mm thick with 20 mm nominal size stone aggregate	Sqm	3.00		

**Eng.-In-Charge**

<u>11</u>	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	Sqm	10.00		
<u>12</u>	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineerin-charge. The sheet shall be fixed using self drilling / self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required	Sqm	8.00		
<u>13</u>	CEMENT PLASTER (IN COARSE SAND) 12 mm cement plaster of mix : 13.4.1 1:4 (1 cement: 4 coarse sand)	Sqm	20.00		
<u>14</u>	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : 13.61.1 Two or more coats on new work	Sqm	10.00		
<u>15</u>	Supplying and stacking at site. 16.3.9 Good earth	Cum	55.00		
				Total Rs.	

**Eng.-In-Charge**