

**Sant Longowal Institute of Engineering and Technology,
Longowal, Distt. Sangrur
(Deemed to be University)
(Established by Govt. of India)**

Quotation Notice

Quotation are invited from working contractors registered with CPWD, State PWD, MES, PUDA/Central Public Sector undertaking having valid license under Contractor Labour (Regulation & Abolition) Act, 1970 and experience of having successfully completed works during the last 7 years ending last day of the month previously to one in which applications are invited:

Three similar completed work each costing not less than the amount equal to 40% of estimated cost put to tender or Two similar completed works, each costing not less than the amount equal to 60% of the estimated cost put to tender or One similar completed work of costing not less than the amount equal to 80% of the estimated cost put to tender with some Central Government Department/State Government Department/Central Autonomous Body/Central Public Sector undertaking.

Sr. No.	Name of Work	DNIT Amount (Rs. In Rupees)	Earnest Money Deposit is 2% of the DNIT amount (Rs. in Rupees)	Cost of Quotation Documents in (Non-refundable)	Time Period	Tender processing fee (Rs.)	Schedule of Quantities
1	Provision of Car Parking Shed in Director Residence at SLIET, Longowal.	46,664.00	Nil	Nil	One Month	Nil	Annexure- 'A'

The Quotation documents will be available only on the Institute's website and should be submitted in the estate office (Civil Wing).

Schedule of Quotations

Availability of Quotation for Bidding		Last date of Submission of Quotation	Date and time of opening of Quotation in Estate Office, SLIET, Longowal
From	To		
21.02.2018	28.02.2018	28.02.2018 before 5:00 PM	01.03.2018 at 12: 30 PM

Eng.-In-Charge

Name of Work: Provision of Car Parking Shed in Director Residence at SLIET, Longowal.

<u>S.No.</u>	<u>DESCRIPTION OF ITEM</u>	<u>UNIT</u>	<u>QTY.</u>	<u>RATE</u>	<u>AMOUNT</u>
1	Surface dressing of the ground including removing vegetation and inequalities not exceeding 15 cm deep and disposal of rubbish, lead up to 50 m and lift up to 1.5 m. All kinds of soil	Sqm	9.02		
2	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : (1 Cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size)	Cum	1.48		
3	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing : 1:1 ½:3 (1 cement : 1½ coarse sand (zone-III) : 3 graded stone aggregate 20 mm nominal size	Cum	0.24		
4	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	Kg	181.00		
5	Providing and fixing pre-coated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	Sqm	18.00		
6	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade : Two or more coats on new work	Sqm	15.00		
7	Providing and laying at or near ground level factory made kerb stone of M-25 grade cement concrete in position to the required line, level and curvature, jointed with cement mortar 1:3 (1 cement: 3 coarse sand), including making joints with or without grooves (thickness of joints except at sharp curves shall not be more than 5mm), including making drainage opening wherever required complete etc. as per direction of Engineer-in-charge (length of finished kerb edging shall be measured for payment). (Precast C.C. kerb stone shall be approved by Engineer-in-charge).	Cum	0.26		

Eng.-In-Charge

8	<p>Providing and laying factory made coloured chamfered edge CementConcrete paver blocks of required strength, thickness & size/shape, madeby table vibratory method using PU mould, laid in required colour & patternover 50mm thick compacted bed of fine sand, compacting and properembedding/laying of inter locking paver blocks into the sand bedding layerthrough vibratory compaction by using plate vibrator, filling the joints withjamuna sand and cutting of paver blocks as per required size and pattern,finishing and sweeping extra sand in footpath, parks, lawns, drive ways orlight traffic parking etc. complete as per manufacturer's specifications &direction of Engineerin-Charge. 60mm thick C.C. paver block of M-35grade with approved colour, design & pattern</p>	Sqm	18.00		
				Total Rs.	

Eng.-In-Charge