

**Sant Longowal Institute of Engineering and Technology,
Longowal, Distt. Sangrur
(Deemed to be University)
(Established by Govt. of India)**

Quotation Notice

Quotation are invited from working contractors registered with CPWD, State PWD, MES, PUDA/Central Public Sector undertaking having valid license under Contractor Labour (Regulation & Abolition) Act, 1970 and experience of having successfully completed works during the last 7 years ending last day of the month previously to one in which applications are invited:


Three similar completed work each costing not less than the amount equal to 40% of estimated cost put to quotation or Two similar completed works, each costing not less than the amount equal to 60% of the estimated cost put to quotation or One similar completed work of costing not less than the amount equal to 80% of the estimated cost put to quotation with some Central Government Department/State Government Department/Central Autonomous Body/Central Public Sector undertaking.

Sr. No.	Name of Work	DNIQ Amount (Rs. In Rupees)	Earnest Money Deposit is 2% of the DNIT amount (Rs. in Rupees)	Cost of Quotation Documents in (Non-refundable)	Time Period	Tender processing fee (Rs.)	Schedule of Quantities
1	Establishment of Centralized Computing Facility on the first floor of Mechanical Block (Extension) under TEQIP-III at SLIET, Longowal	8,86,012.00	Nil	Nil	03 Months	Nil	Annexure-'A'

The Quotation documents will be available only on the Institute's website and should be submitted in the estate office (Civil Wing).

Schedule of Quotations

Availability of Quotation for Bidding		Last date of Submission of Quotation	Date and time of opening of Quotation in Estate Office, SLIET, Longowal
From	To		
09.04.2019	23.04.2019	23.04.2019 before 5:00 PM	24.04.2019 at 11:00 AM



Eng.-In-Charge

**Name of Work: Establishment of Centralized Computing Facility on the first floor of Mechanical Block (Extension) under
TEQIP-III at SLIET, Longowal.**

S.No.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
1	Providing and fixing in position collapsible steel shutters with vertical channels 20x10x2 mm and braced with flat iron diagonals 20x5 mm size, with top and bottom rail of T-iron 40x40x6 mm, with 40 mm dia steel pulleys, complete with bolts, nuts, locking arrangement, stoppers, handles, including applying a priming coat of approved steel primer.	Sqm	30.00		
2	Providing and laying Vitrified tiles in different sizes (thickness to be specified by the manufacturer), with water absorption less than 0.08% and conforming to IS: 15622, of approved brand & manufacturer, in all colours and shade, in skirting, riser of steps, laid with cement based high polymer modified quick set tile adhesive (water based) conforming to IS: 15477, in average 6 mm thickness, including grouting of joints (Payment for grouting of joints to be made separately). 11.47.2 Size of Tile 600x600 mm	sqm	2.00		
3	Providing and laying Vitrified tiles in floor with different sizes (thickness to be specified by the manufacturer), with water absorption less than 0.08% and conforming to IS:15622, of approved brand & manufacturer, in all colours and shade, laid with cement based high polymer modified quick set tile adhesive (water based) conforming to IS : 15477, in average 6 mm thickness, including grouting of joints (Payment for grouting of joints to be made separately). Size of Tile 600x600 mm	sqm	45.00		
4	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade : Old work (one or more coats)	Sqm	400.00		
5	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	Sqm	100.00		
6	Steel work welded in built up sections/ framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required. In gratings, frames, guard bar , ladder , railings, bracket s, gates and similar works	Kg	70.00		
7	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade : Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture	Sqm	80.00		
8	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per directions of Engineer-In-Charge. With cement mortar 1:4 (1cement: 4 coarse sand)	Sqm	90.00		


Eng.-In-Charge

9	Providing and fixing anodised aluminium grill (anodised transparent or dyed to required shade according to IS: 1868 with minimum anodic coating of grade AC 15) of approved design/pattern, with approved standard section and fixed to the existing window frame with C.P . brass/ stainless steel screws @ 200 mm centre to centre, including cutting the grill to proper opening size for fixing and operation of handles and fixing approved anodised aluminium standard section around the opening, all complete as per requirement and direction of Engineer-in-charge. (Only weight of grill to be measured for payment).	Kg	102.00		
10	Providing and fixing mineral fibre false ceiling tiles at all heights of size 595X595mm of approved texture, design and pattern. The tiles should have Humidity Resistance (RH) of 99%, Light Reflectance >85%, Thermal Conductivity $k = 0.052 - 0.057 \text{ w/m K}$, Fire Performance as per (BS 476 pt - 6 & 7) in true horizontal level suspended on interlocking T -Grid of hot dipped all round galvanized iron section of 0.33 mm thick (galvanized @120 gsm) comprising of main T runners of 15x32 mm of length 3000 mm, cross T of size 15x32mm of length 1200 mm and secondary intermediate cross T of size 15x32 mm of length 600 mm to form grid module of size 600x600 mm suspended from ceiling using galvanized mild steel item (galvanised @80gsm) 50 mm long 8mm outer diameter M-6 dash fasteners, 6 mm diameter fully threaded hanger rod upto 1000 mm length and L-shape level adjuster of size 85x25x2 mm, spaced at 1200 mm centre to centre along main 'T'. The system should rest on periphery walls /partitions with the help of GI perimeter wall angle of size 24x24X3000 mm made of 0.40 mm thick sheet, to be fixed to the wall with help of plastic rawl plug at 450 mm centre to centre & 40 mm long dry wall S.S. screws. The exposed bottom portion of all T-sections used in false ceiling support system shall be preprinted with polyester baked paint, for all heights. The work shall be carried out as per specifications, drawings and as per directions of the engineer-in-charge. With 16 mm thick beveled tegular mineral fibre false ceiling tile (NRC 0.55 to 0.6)	Sqm	301.00		
11	Refixing of Aluminum Doors all complete	Each	4.00		
12	Taking out of Aluminum Doors all complete	Each	4.00		
13	Providing and installations vanitial blind at windows.	Sqm	40.00		
				Total Rs.	


Eng.-In-Charge