Sant Longowal Institute of Engineering and Technology, Longowal, Distt. Sangrur (Deemed to be University) (Established by Govt. of India)

Ouotation Notice

Quotation are invited from working contractors registered with CPWD, State PWD, MES, PUDA/Central Public Sector undertaking having valid license under Contractor Labour (Regulation & Abolition) Act, 1970 and experience of having successfully completed works during the last 7 years ending last day of the month previously to one in which applications are invited:

Three similar completed work each costing not less than the amount equal to 40% of estimated cost put to tender or Two similar completed works, each costing not less than the amount equal to 60% of the estimated cost put to tender or One similar completed work of costing not less than the amount equal to 80% of the estimated cost put to tender with some Central Government Department/State Government Department/Central Autonomous Body/Central Public Sector undertaking.

Sr. No.	Name of Work	DNIT Amount (Rs. In Rupees)	Earnest Money Deposit is 2% of the DNIT amount (Rs. in Rupees)	Cost of Quotation Documents in (Non- refundable)	Time Period	Tender processin g fee (Rs.)	Schedule of Quantities
1	Repair of false ceiling in Main Auditorium building at SLIET, Longowal.	99,964.0 0	Nil	Nil	20 days	Nil	Annexure- 'A'

The Quotation documents will be available only on the Institute's website and should be submitted in the estate office (Civil Wing).

Schedule of Quotations

Availability of Quotation for Bidding		Last date of Submission of Quotation	Date and time of opening of Quotation in Estate Office, SLIET,		
From	То		Longowal		
24.07.2023	023 28.07.2023	28.07.2023	28.07.2023		
27.07.2023		before 10:00 AM	at 11:00 AM		

The tenderer should attach proofs of the following documents

- Valid license under the Contract Labour (Regulation & Abolition) Act.1970 of the last work successfully (i) completed
- Proof of registration with EPFO & E.P.F. Account No. (ii)
- Proof of registration with ESIC & ESI Account No. (iii)
- (iv) **PAN Number**
- Goods & Service Tax (GST) registration number (v)
- Last three consecutive Income Tax Returns (vi)
- (vii) Eligibility related documents & other certificate i.e. Experience Certificate and work order/letter of award of the work issued by the department etc.
- (viii) Appropriate class enlistment as civil contractors registered with CPWD, State PWD, MES, PUDA/Central Public Sector, state Govt. /PSU undertaking.

Eng.-In-Charge

Annexure- 'A'

No.	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT
1	Providing and fixing double scaffolding system (cup lock				
-	type) on the exterior side, up to seven story height made				
	with 40 mm dia M.S. tube 1.5 m centre to centre,				
	horizontal & vertical tubes joining with cup & lock				
	system with M.S. tubes, M.S. tube challies, M.S. clamps				
	and M.S. staircase system in the scaffolding for working				
	platform etc. and maintaining it in a serviceable				
	condition for the required duration as approved and				
	removing it there after .The scaffolding system shall be				
	stiffened with bracings, runners, connection with the				
	building etc wherever required for inspection of work at				
	required locations with essential safety features for the				
	workmen etc. complete as per directions and approval				
	of Engineerin-charge The elevational area of the				
	scaffolding shall be measured for payment purpose. The				
	payment will be made once irrespective of duration of				
	scaffolding.				
	Note: - This item to be used for maintenance work				
	judicially, necessary deduction for scaffolding in the				
	existing item to be done.	Sqm	288.00		
2	Providing and fixing mineral fibre false ceiling tiles at all	oqin	200.00		
-	heights of size 595X595mm of approved texture, design				
	and pattern. The tiles should have Humidity Resistance				
	(RH) of 99%, Light Reflectance ? 85%, Thermal				
	Conductivity $k = 0.052 - 0.057$ w/m K, Fire Performance				
	as per (BS 476 pt - 6 &7)in true horizontal level				
	suspended on interlocking T-Grid of hot dipped all				
	round galvanized iron section of 0.33 mm thick				
	(galvanized @120 gsm) comprising of main T runners of				
	15x32 mm of length 3000 mm, cross T of size 15x32mm				
	of length 1200 mm and secondary intermediate cross T				
	of size 15x32 mm of length 600 mm to form grid module				
	of size 600x600 mm suspended from ceiling using				
	galvanized mild steel item (galvanised@80gsm) 50 mm				
	long 8mm outer diameter M-6 dash fasteners, 6 mm				
	diameter fully threaded hanger rod up to 1000 mm				
	length and L-shape level adjuster of size 85x25x2 mm,				
	spaced at 1200 mm centre to centre along main 'T'. The				
	system should rest on periphery walls /partitions with				
	the help of GI perimeter wall angle of size24x24X3000				
	mm made of 0.40 mm thick sheet, to be fixed to the wall				
	with help of plastic rawl plug at 450 mm centre to				
	centre & 40 mm long dry wall S.S. screws. The exposed				
	bottom portion of all T-sections used in false ceiling				
	support system shall be pre-painted with polyester				
	baked paint, for all heights. The work shall be carried				
	out as per specifications, drawings and as per directions				
	of the engineer-in-charge.26.27.1 With 16 mm thick				
	beveled tegular mineral fibre false ceiling tile (NRC 0.55	Carro	0.01		
	to 0.6	Sqm	8.64		An
				Total Rs.	



, · •